



| Model Number | Nominal Size (Inches) W x H x D | Actual Size (Inches) W x H x D | Rated Air Flow (CFM) | Initial Resistance (IN W.G.) | Media Area (Square Feet) |
|---------------|------------------------------------|-----------------------------------|----------------------|------------------------------|--------------------------|
| DPGT-STD2-220 | 12 x 20 x 2 | 11-3/4 x 19-3/4 x 1-3/4 | 1040 | .40 | 7.3 |
| DPGT-STD2-210 | 12 x 24 x 2 | 11-3/8 x 23-3/8 x 1-3/4 | 1250 | .40 | 8.6 |
| DPGT-STD2-239 | 14 x 20 x 2 | 13-3/4 x 19-3/4 x 1-3/4 | 1215 | .40 | 8.8 |
| DPGT-STD2-241 | 14 x 25 x 2 | 13-3/4 x 24-3/4 x 1-3/4 | 1520 | .40 | 11.0 |
| DPGT-STD2-245 | 15 x 20 x 2 | 14-3/4 x 19-3/4 x 1-3/4 | 1300 | .40 | 9.3 |
| DPGT-STD2-201 | 16 x 20 x 2 | 15-1/2 x 19-1/2 x 1-3/4 | 1400 | .40 | 9.9 |
| DPGT-STD2-202 | 16 x 25 x 2 | 15-1/2 x 24-1/2 x 1-3/4 | 1740 | .40 | 12.3 |
| DPGT-STD2-280 | 18 x 20 x 2 | 17-3/4 x 19-3/4 x 1-3/4 | 1560 | .40 | 10.9 |
| DPGT-STD2-212 | 18 x 24 x 2 | 17-1/2 x 23-1/2 x 1-3/4 | 1875 | .40 | 13.0 |
| DPGT-STD2-285 | 18 x 25 x 2 | 17-1/2 x 24-1/2 x 1-3/4 | 1950 | .40 | 13.6 |
| DPGT-STD2-203 | 20 x 20 x 2 | 19-1/2 x 19-1/2 x 1-3/4 | 1740 | .40 | 11.9 |
| DPGT-STD2-211 | 20 x 24 x 2 | 19-3/8 x 23-3/8 x 1-3/4 | 2080 | .40 | 14.2 |
| DPGT-STD2-204 | 20 x 25 x 2 | 19-1/2 x 24-1/2 x 1-3/4 | 2170 | .40 | 14.9 |
| DPGT-STD2-205 | 24 x 24 x 2 | 23-3/8 x 23-3/8 x 1-3/4 | 2500 | .40 | 17.6 |
| DPGT-STD2-225 | 25 x 25 x 2 | 24-1/2 x 24-1/2 x 1-3/4 | 2710 | .40 | 19.4 |
| DPGT-STD4-410 | 12 x 24 x 4 | 11-3/8 x 23-3/8 x 3-3/4 | 1040 | .26 | 12.4 |
| DPGT-STD4-401 | 16 x 20 x 4 | 15-1/2 x 19-1/2 x 3-3/4 | 1400 | .26 | 14.6 |
| DPGT-STD4-402 | 16 x 25 x 4 | 15-1/2 x 24-1/2 x 3-3/4 | 1740 | .26 | 18.3 |
| DPGT-STD4-412 | 18 x 24 x 4 | 17-1/2 x 23-1/2 x 3-3/4 | 1875 | .26 | 19.9 |
| DPGT-STD4-403 | 20 x 20 x 4 | 19-1/2 x 19-1/2 x 3-3/4 | 1740 | .26 | 18.8 |
| DPGT-STD4-411 | 20 x 24 x 4 | 19-3/8 x 23-3/8 x 3-3/4 | 2080 | .26 | 22.4 |
| DPGT-STD4-404 | 20 x 25 x 4 | 19-1/2 x 24-1/2 x 3-3/4 | 2170 | .26 | 23.5 |
| DPGT-STD4-405 | 24 x 24 x 4 | 23-3/8 x 23-3/8 x 3-3/4 | 2500 | .26 | 26.1 |

STANDARD CONSTRUCTION

- 100% Synthetic Media, White
- Expanded Metal Pleat Backing
- Moisture Resistant Beverage Board Frame
- Double Wall Frame
- (2) Rows of Fingers on Air Entering Side (2" Depth)
- (2) Rows of Fingers on Air Leaving Side (4" Depth)

NOTES

- MERV 8 ASHRAE 52.2-2007
- Final Resistance: 1.0" W.G.
- Rated Velocity: 625 FPM
- Class 2 Filter Per U.L. Standard 900
- Maximum Operating Temperature: 200 deg. F



P.O. Box 32578
Louisville, KY 40232
P: 866-247-4827
F: 502-961-0930
www.airguard.com

**CONTACT FACTORY TO
VERIFY REVISION LEVEL**

**TOLERANCES
UNLESS OTHERWISE SPECIFIED**

- FRACTIONAL -
DECIMAL -
ANGLES -

ALL DIMENSIONS IN INCHES

DRAWING NAME: **TYPE DP-GT GAS TURBINE PLEAT**

APPROVED BY: *H. Quinn* SPECIFICATION NO.: **MKT-B-00165** PAGE: **1 OF 1**

SCALE: **NONE** DWG. SIZE: **A** REVISION: **G** REVISION DATE: **03-31-11**

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLC AIR. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.