



Model Number	Nominal Size (Inches) W x H	Wire Size (Inches) W x H	Number Of Cross Wires	Initial Resistance (Inches W.G.)	
				300 FPM	500 FPM
IN-117	10 x 20	9-1/2 x 19-1/2	1	.18	.40
IN-110	12 x 24	11-3/8 x 23-3/8	2	.18	.40
IN-145	15 x 20	14-1/2 x 19-1/2	1	.18	.40
IN-101	16 x 20	15-1/2 x 19-1/2	1	.18	.40
IN-116	16 x 24	15-3/8 x 23-3/8	2	.18	.40
IN-102	16 x 25	15-1/2 x 24-1/2	2	.18	.40
IN-112	18 x 24	17-3/8 x 23-3/8	2	.18	.40
IN-161	20 x 16	19-1/2 x 15-1/2	1	.18	.40
IN-103	20 x 20	19-1/2 x 19-1/2	1	.18	.40
IN-111	20 x 24	19-3/8 x 23-3/8	2	.18	.40
IN-104	20 x 25	19-1/2 x 24-1/2	2	.18	.40
IN-106	24 x 12	23-3/8 x 11-3/8	1	.18	.40
IN-144	24 x 16	23-3/8 x 15-3/8	1	.18	.40
IN-115	24 x 20	23-3/8 x 19-3/8	1	.18	.40
IN-105	24 x 24	23-3/8 x 23-3/8	2	.18	.40
IN-165	25 x 16	24-1/2 x 15-1/2	1	.18	.40
IN-152	25 x 20	24-1/2 x 19-1/2	1	.18	.40
IN-125	25 x 25	24-1/2 x 24-1/2	2	.18	.40

STANDARD CONSTRUCTION:

1. Polyester Media
 - 1/2" P-50 Air Entering Side (White)
 - 1/2" P-50 Tackified Air Leaving Side (White)
2. Heat Seal Construction
3. 9 GA Steel Internal Wire Frame
4. Cross Wires Installed in the Width Direction

NOTES:

1. MERV 6 ASHRAE 52.2-1999
2. Final Resistance: 1.0" W.G.
3. Class 2 Filter Per U.L. Standard 900
4. Maximum Operating Temperature: 220 deg. F



1612 N DAVIS AVE
OTTAWA, KS 66067
P: 800-624-8739
F: 785-242-8700

CONTACT FACTORY TO
VERIFY REVISION LEVEL

TOLERANCES
UNLESS OTHERWISE SPECIFIED

FRACTIONAL +/- 1/8"
DECIMAL -
ANGLES -

ALL DIMENSIONS IN INCHES

DRAWING NAME

SERIES N 2-PLY RING PANEL FILTER

APPROVED BY

[Signature]

SPECIFICATION NO.

MKT-B-00290

PAGE

1 OF 1

SCALE

NONE

DWG. SIZE

A

REVISION

D

REVISION DATE

11-16-06

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLARDOR AIR FILTRATION. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.