



Item Number	Description	Length (L) (Inches)	Media Area (Square Feet)	Bolt Hole Dia. (D) (Inches)	Note	Media Type
1279215	AG61-9215-109	26	226	0.540	4	Cellulose / Polyester
1279213	AG61-9215-109-FR	26	226	0.540	4	Cellulose / Polyester
1279233	AG61-9230-109	30	260	0.540	4	Cellulose / Polyester
1279206	AG61-9230-109-FR	30	260	0.540	4	Cellulose / Polyester
1215858	AG61-5858-109-LBH	22	191	1.187	5	Cellulose / Polyester
	AG61-5858-104-LBH	22	191	1.187	5	Synthetic
1279217	AG61-9215-109-LBH	26	226	1.187	5	Cellulose / Polyester
1279208	AG61-9215-109-FR-LBH	26	226	1.187	5	Cellulose / Polyester

#### NOTES

- Maximum Temperature: 180 deg. F
- Top & Bottom End caps:  
22 GA Electro Galvanized  
Open/Closed with Bolt Hole
- Inner & Outer Retainers:  
22 GA Electro Galvanized Expanded Metal  
72% Open Area
- Washer Supplied with 0.540" Bolt Hole Cartridge
- Washer Not Supplied on LBH Style Cartridge
- FR Denotes Fire Retardant Media



ONE SOURCE  
FOR  
AIR FILTRATION  
PRODUCTS

P.O. Box 32578  
Louisville, KY 40232  
P: 502-969-2304  
F: 502-961-0930

CONTACT FACTORY TO  
VERIFY REVISION LEVEL

TOLERANCES  
UNLESS OTHERWISE SPECIFIED

FRACTIONAL  
DECIMAL  
ANGLES

ALL DIMENSIONS IN INCHES

DRAWING NAME

OPEN-CLOSED W/BOLT HOLE 12.75 OD

APPROVED BY

*K. Quinn*

SPECIFICATION NO.

MKT-B-00395

PAGE

1 OF 1

SCALE

NONE

DWG. SIZE

A

REVISION

C

REVISION DATE

03-02-04

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY AIRGUARD. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.