



NOTES

1. Maximum Temperature: 150 deg. F
2. Top & Bottom End caps:
22 GA Electro Galvanized
Open/Closed with No Bolt Hole
3. Inner & Outer Retainers:
22 GA Electro Galvanized Expanded Metal
72% Open Area
4. 3 Stage Synthetic Wrap Included
5. Wrap Secured to Cartridge with Velcro Strip
Where Noted

Item Number	Description	Diameter (OD) (Inches)	Length (L) (Inches)	Media Area (Square Feet)	Torit Number	See Note #
1289652	AG32-9652-104	10.87	8	41	3EA-39652-01	
1243587	AG32-3587-104	16	12	82	3EA-35877-01	5
1283588	AG32-3588-104	18.75	20	140	3EA-35877-02	5
1283589	AG32-3589-104	22.25	25	220	3EA-35877-03	5



P.O. Box 32578
Louisville, KY 40232
P: 502-969-2304
F: 502-961-0930

**CONTACT FACTORY TO
VERIFY REVISION LEVEL**

**TOLERANCES
UNLESS OTHERWISE SPECIFIED**

FRACTIONAL
DECIMAL
ANGLES

ALL DIMENSIONS IN INCHES

DRAWING NAME

TORIT DRYFLO REPLACEMENT CARTRIDGE

APPROVED BY *H. Quinn*

SPECIFICATION NO.
MKT-B-00414

PAGE
1 OF 1

SCALE
NONE

DWG. SIZE
A

REVISION
A

REVISION DATE
11-12-03

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY AIRGUARD. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.